

Refrigeration Oil 68

DESCRIPTION:

Refrigeration Oil 68 is a high performance naphthenic mineral oils specifically manufactured for use in refrigeration and air conditioning compressors when refrigerants other than HFCs are used. They have very low pour points and are compatible with all refrigerants except hydrofluorocarbons (HFCs).

FEATURES/BENEFITS:

- Wax free formulation reduces down time
- Excellent lubricity guards against wear
- Ensures evaporator tubes are kept clean
- Good chemical stability for seal compatibility
- Excellent thermal stability resists deposit formation
- Multi-purpose lubricant for both cylinders and bearings

APPLICATIONS:

Refrigeration Oil 68 is recommended for cylinder and bearing lubrication in reciprocating and rotary refrigeration compressors. They are also recommended for use in air conditioning systems without HFC refrigerants. They can also be used in most other machinery operating at sub-zero temperatures.

* ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

ISO GRADE	68
Specific Gravity @ 60 °F	0.9134
Viscosity, Kinematic cSt at 40°C Min/Max cSt at 100°C	61.2 – 74.8 7.1
Viscosity Index	45
Flash Point, °F	330
Pour Point, °C (°F)	-37 (-35)
Color	1.0

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.